


Outline Drawing and Circuit Diagram

Dim.	Inches	Millimeters	Dim.	Inches	Millimeters
A	4.33	110.0	R	0.20	5.1
B	3.15	80.0	S	0.14 Min.	3.6 Min.
C	0.87	22.0	T	0.22 Dia.	5.6 Dia.
D	3.74±0.01	95.0±0.25	U	M6 Metric	M6
E	2.60±0.01	66.0±0.25	V	M4 Metric	M4
F	2.01	51.0	W	1.38+0.04/-0.02	35.0+1.0/-0.5
G	1.50	38.0	X	1.18+0.04/-0.02	30.0+1.0/-0.5
H	0.72	18.3	Y	0.43	11.0
J	0.20	5.0	Z	0.06	1.5
K	0.28	7.0	AA	0.16	4.0
L	0.12	3.0	AB	0.09	2.35
M	0.31	8.0	AC	0.67	17.0
N	0.83	21.0	AD	0.55	14.0
P	1.02	26.0	AE	0.45	11.4
Q	0.54	13.7	AF	0.35	9.0

#### Ordering Information:

Example: Select the complete module number you desire from the table - i.e. CM300YE2N-12F and CM300YE2P-12F are 600V ( $V_{CES}$ ), 300 Ampere TLI-Series IGBT Power Modules.

Type	Current Rating Amperes	$V_{CES}$ Volts (x 50)
CM	300	12



#### Description:

The TLI-Series has been designed for three level (neutral point clamped) topologies in applications requiring high efficiency operation and improved output waveform quality. They also provide significant benefits in applications where low output noise using small filter components is required or where long motor leads create Standing Wave Ratio (SWR) voltage surge issues.

#### Features:

- Smaller Output Voltage Steps Reducing Surge Voltage
- Low Output Ripple Current
- Lower Modulation Frequency With Same Quality Output Waveform

#### Applications:

- Three Level Inverter Topologies
- Solar Power Inverters
- High Efficiency UPS
- Long Motor Lead Applications



Powerex, Inc., 173 Pavilion Lane, Youngwood, Pennsylvania 15697 (724) 925-7272 www.pwr.com

CM300YE2N-12F / CM300YE2P-12F  
TLI-Series (Three Level Inverter) IGBT  
300 Amperes/600 Volts

### Absolute Maximum Ratings, $T_j = 25^\circ\text{C}$ unless otherwise specified

Ratings	Symbol	CM300YE2N-12F / CM300YE2P-12F	Units
Junction Temperature	$T_j$	-40 to 150	$^\circ\text{C}$
Storage Temperature	$T_{stg}$	-40 to 125	$^\circ\text{C}$
Mounting Torque, Main Terminals (C1, AK, E2), M8 Screw (Max.)	–	40	in-lb
Mounting Torque, Mounting Holes, M5 Screw (Max.)	–	30	in-lb
Mounting Torque, C2, E1 Terminals, M4 Screw (Max.)	–	15	in-lb
Weight (Typical)	–	530	Grams
Isolation Voltage (Main Terminal to Baseplate, AC 1 min.)	$V_{iso}$	2500	$V_{rms}$

### Inverter Part

Collector-Emitter Voltage (G-E Short)	$V_{CES}$	600	Volts
Gate-Emitter Voltage (C-E Short)	$V_{GES}$	$\pm 20$	Volts
Collector Current DC ( $T_C = 25^\circ\text{C}$ )	$I_C$	300	Amperes
Peak Collector Current (Pulse) <sup>*2</sup>	$I_{CM}$	600	Amperes
Emitter Current ( $T_C = 25^\circ\text{C}$ )	$I_E^{*1}$	300	Amperes
Peak Emitter Current (Pulse) <sup>*2</sup>	$I_{EM}^{*1}$	600	Amperes
Maximum Collector Dissipation ( $T_C = 25^\circ\text{C}$ )	$P_C^{*3}$	960	Watts

### Clamp Diode Part

Repetitive Peak Reverse Voltage	$V_{RRM}$	600	Volts
Forward Current ( $T_C = 25^\circ\text{C}$ )	$I_{FM}$	300	Amperes

\*1  $I_E$ ,  $I_{EM}$ ,  $V_{EC}$ ,  $t_{rr}$ , and  $Q_{rr}$  represent characteristics of the anti-parallel, emitter-to-collector free-wheel diode (FWDi).

\*2 Pulse width and repetition rate should be such that device junction temperature ( $T_j$ ) does not exceed  $T_{j(max)}$  rating.

\*3 Junction temperature ( $T_j$ ) should not increase beyond  $150^\circ\text{C}$ .

**CM300YE2N-12F / CM300YE2P-12F**  
**TLI-Series (Three Level Inverter) IGBT**  
 300 Amperes/600 Volts

**Electrical Characteristics,  $T_j = 25^\circ\text{C}$  unless otherwise specified**

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
<b>Inverter Part</b>						
Collector-Cutoff Current	$I_{CES}$	$V_{CE} = V_{CES}, V_{GE} = 0V$	–	–	1	mA
Gate-Emitter Threshold Voltage	$V_{GE(th)}$	$I_C = 30mA, V_{CE} = 10V$	5	6	7	Volts
Gate Leakage Current	$I_{GES}$	$V_{GE} = V_{GES}, V_{CE} = 0V$	–	–	40	$\mu A$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 300A, V_{GE} = 15V, T_j = 25^\circ\text{C}$	–	1.6	2.2	Volts
		$I_C = 300A, V_{GE} = 15V, T_j = 125^\circ\text{C}$	–	1.6	–	Volts
Input Capacitance	$C_{ies}$		–	–	81	nF
Output Capacitance	$C_{oes}$	$V_{CE} = 10V, V_{GE} = 0V$	–	–	5.4	nF
Reverse Transfer Capacitance	$C_{res}$		–	–	3.0	nF
Total Gate Charge	$Q_G$	$V_{CC} = 300V, I_C = 300A, V_{GE} = 15V$	–	1860	–	nC
Turn-on Delay Time	$t_{d(on)}$	$V_{CC} = 300V, I_C = 300A,$	–	–	600	ns
Turn-on Rise Time	$t_r$	$V_{GE1} = V_{GE2} = 15V,$	–	–	400	ns
Turn-off Delay Time	$t_{d(off)}$	$R_G = 6.2\Omega,$	–	–	1100	ns
Turn-off Fall Time	$t_f$	Inductive Load Switching Operation,	–	–	300	ns
Reverse Recovery Time	$t_{rr}^{*1}$	$I_E = 300A$	–	–	200	ns
Reverse Recovery Charge	$Q_{rr}^{*1}$		–	3.5	–	$\mu C$
Emitter-Collector Voltage	$V_{EC}^{*1}$	$I_E = 300A, V_{GE} = 0V$	–	–	2.8	Volts
External Gate Resistance	$R_G$		6.2	–	21	$\Omega$

**Clamp Diode Part**

Repetitive Reverse Current	$I_{RRM}$	$V_R = V_{RRM}$	–	–	1	mA
Forward Voltage Drop	$V_{FM}$	$I_F = 300A$	–	–	2.8	Volts
Reverse Recovery Time	$t_{rr}$	$I_F = 300A, V_{CC} = 300V,$	–	–	200	ns
Reverse Recovery Charge	$Q_{rr}$	$V_{GE1} = V_{GE2} = 15V, R_G = 6.2\Omega,$ Inductive Load Switching Operation	–	3.5	–	$\mu C$

**Thermal and Mechanical Characteristics,  $T_j = 25^\circ\text{C}$  unless otherwise specified**

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance, Junction to Case <sup>*4</sup>	$R_{th(j-c)Q}$	Inverter IGBT	–	–	0.13	$^\circ\text{C/W}$
Thermal Resistance, Junction to Case <sup>*4</sup>	$R_{th(j-c)D}$	Inverter FWDi	–	–	0.19	$^\circ\text{C/W}$
Thermal Resistance, Junction to Case <sup>*4</sup>	$R_{th(c-f)D}$	Clamp Diode Part	–	–	0.19	$^\circ\text{C/W}$
Contact Thermal Resistance <sup>*4*5</sup>	$R_{th(c-f)}$	Thermal Grease Applied (per 1 Module)	–	0.037	–	$^\circ\text{C/W}$










<sup>\*4</sup>  $T_C$  measured point is just under the chips. If using this value,  $R_{th(f-a)}$  should be measured just under the chips.

<sup>\*5</sup> Typical value is measured by using thermally conductive grease of  $\lambda = 0.9 [W/(m \cdot K)]$ .



Powerex, Inc., 173 Pavilion Lane, Youngwood, Pennsylvania 15697 (724) 925-7272 www.pwr.com

CM300YE2N-12F / CM300YE2P-12F  
 TLI-Series (Three Level Inverter) IGBT  
 300 Amperes/600 Volts



**CM300YE2N-12F / CM300YE2P-12F**  
**TLI-Series (Three Level Inverter) IGBT**  
 300 Amperes/600 Volts

