

**SANSHA ELECTRIC MFG. CO., LTD.**

Web: [www.sansha.co.jp/](http://www.sansha.co.jp/) E-mail [sales@sansha.co.jp](mailto:sales@sansha.co.jp)

**Headquarters**

3-1-56, Nishiawaji, Higashiyodogawa-ku, Osaka 533-0031, Japan  
Tel:+81-6-6325-3863 Fax:+81-6-6321-1536

**Branches and Business Offices**

Tokyo, Nagoya, Kyushu

**Overseas Offices and Affiliates**

**SANREX CORPORATION [U.S.A]**

50 Seaview Boulevard Port Washington, N.Y. 11050-4618  
Tel:+1-516-625-1313 Fax:+1-516-625-8845

**SANREX CORPORATION REPRESENTATIVE OFFICE EUROPE [Slovenia]**

Tel:+386-1514-0793 Fax:+386-1514-0795

**SANREX ASIA PACIFIC PTE. LTD. [Singapore]**

Tel:+65-6457-8867, Fax:+65-6459-6425

**SANREX LIMITED [Hongkong]**

Tel:+852-2744-1310, +852-2785-6313 Fax:+852-2785-6009

**SANSHA ELECTRIC MFG (SHANGHAI) CO., LTD. [China]**

Tel:+86-21-5868-1058, Fax:+86-21-5868-1056

**SANREX KOREA OFFICE [Korea]**

Tel:+82-2-552-2803, Fax:+82-2-552-8441

**SANREX TAIWAN OFFICE [Taiwan]**

Tel:+886-2-2543-5689, Fax:+886-2-2536-7876

●Appearance and specifications are subject to change without any notice.

**S E M I C O N D U C T O R** Products Catalog

SANSHA ELECTRIC MFG. CO., LTD.

# CONTENTS

■SYMBOLS & TERMS	2
■SELECTION GUIDE	3

---

## POWER MODULE

■PRODUCT FEATURES	4
■TYPE DESIGNATION	4
■DIODE / FRD / SBD	
SOFT RECOVERY DIODE	5
FAST RECOVERY DIODE	5
SHOTTKY BARRIER DIODE	5
RECTIFIER DIODE DD/KD SERIES	5
3-PHASE DIODE DF-NA SERIES	5
3-PHASE DIODE DF-AC SERIES	6
3-PHASE DIODE DF-AA/BA/CA SERIES	6
3-PHASE DIODE DF-LA/LB SERIES	6
3-PHASE DIODE+THYRISTOR DFA SERIES	6
■THYRISTOR	
THYRISTOR AK SERIES	6
HIGH CURRENT THYRISTOR	7
THYRISTOR PK/PD SERIES	7
THYRISTOR SCA/SCE SERIES	7
THYRISTOR PWB SERIES	7

---

## DISCRETE

■PRODUCT FEATURES	8
■TYPE DESIGNATION	8
■TRIAC	
Through Hole Standard	9
Through Hole Sensitive Gate	9
Through Hole Tj max=150°C	9
SMD (Surface Mount Device) Standard	10
SMD (Surface Mount Device) Sensitive Gate	10
SMD (Surface Mount Device) Tj max=150°C	10
Tab terminal Standard	10
■THYRISTOR	
Through Hole Standard	10
Through Hole Sensitive Gate	10
SMD (Surface Mount Device) Standard	11
SMD (Surface Mount Device) Sensitive Gate	11
Tab terminal Standard	11
■FRD	11
■DIODE	11


---

■OUTLINE DRAWINGS	12
■PACKAGING SPECIFICATIONS	18

# SYMBOLS & TERMS


FRD		DIODE		THYRISTOR		TRIAC	
Symbol	Terminology	Symbol	Terminology	Symbol	Terminology	Symbol	Terminology
$V_{RRM}$	Repetitive peak reverse voltage	$V_{RRM}$	Repetitive peak reverse voltage	$V_{RRM}$	Repetitive peak reverse voltage	$V_{DRM}$	Repetitive peak off-state voltage
$I_{F(AV)}$	Average Forward Current	$I_{F(AV)}$	Average Forward Current	$V_{DRM}$	Repetitive peak off-state voltage	$I_{T(RMS)}$	RMS on-state current
$V_{FM}$	Peak Forward Voltage	$I^2t$	$I^2t$	$I_{T(AV)}$	Average on-state current	$I_{DRM}$	Repetitive peak off-state voltage
$I_{RRM}$	Repetitive peak reverse current	$V_{FM}$	Peak Forward Voltage	$I_{T(RMS)}$	RMS on-state current	$V_{TM}$	On-state voltage
$T_{rr}$	Reverse Recovery Time	$I_{RRM}$	Repetitive Peak Reverse Current	$I_{DRM}$	Repetitive peak off-state current	$I_{GT}$	Gate trigger current
$I_{FSM}$	Surge forward current	$I_{FSM}$	Surge forward current	$V_{TM}$	On-state voltage	$V_{GT}$	Gate trigger voltage
$T_j$	Junction temperature	$T_j$	Junction temperature	$I_{GT}$	Gate trigger current	$dv/dt(c)$	Critical Rate of Rise of Off-State Voltage at Commutation
$R_{th(j-c)}$	Junction-to-case thermal impedance	$R_{th(j-c)}$	Junction-to-case thermal impedance	$V_{GT}$	Gate trigger voltage	$T_j$	Junction temperature
				$T_j$	Junction temperature	$R_{th(j-c)}$	Junction-to-case thermal impedance
				$R_{th(j-c)}$	Junction-to-case thermal impedance		

## GATE TRIGGER MODE for TRIACS (Quadrant definitions)




# SELECTION GUIDE


## Converter Bridge





## Secondary Rectifier



## 3-Phase Control



## AC Control



# POWER MODULE



## PRODUCT FEATURES

### ► Fast Recovery Diode

SanRex design to minimize switching losses for our fast recovery diodes. And we add the soft recovery diodes with a low noise characteristic to our fast recovery diode line-up.

We can offer the suitable device in applications requiring high efficiency and favorable to the environment.

#### Fast Soft Recovery Series

**DCA Series** Two types of recovery time are available.

**DBA Series** Two types of recovery time and softness are available.

#### Fast Recovery Series

**FRG Series** Low current diode in an easy-to-assemble Tab terminal

**FDF Series** Single phase bridge rectifier

**FRS Series** High current diode up to 400A

**DKR Series** Compact non-isolated package, dual diode common cathode

### ► Diode / Thyristor rectifier

Thyristor: 800V and 1600V models are available; The characteristics of  $dv/dt$  and surge current are suitable for 200V/400V input rectification.

Three phase bridges are offered in different package height, which allow variable layouts with different module packages and improved mounting.

All Sanrex modules are RoHS compliant.

#### DF Series

Three phase bridge rectifier in various case profile

**DF\_AA/BA** : Standard models

**DF\_CA** : High surge current withstand models

**DF\_NA** : Compact SIP(=Single-In-line Package) modules

**DF\_AC** : 17mm low profile modules

**DF\_LA/LB** : LA/LB series are same profile. LB type has partitioned terminals for increased creepage distance

#### DFA Series

Three phase bridge rectifier with built-in thyristor for inrush protection at the positive DC terminal


#### DD / KD Series

Standard dual diode modules, in series (DD), and common cathode (KD)

#### PK/SCA and PD/SCE Series

Standard dual thyristor and thyristor-diode modules

## TYPE DESIGNATION







# DIODE / FRD / SBD

## SOFT RECOVERY DIODE

Viso : 2500V (RMS) Tj(max) : 150°C

Type	VRRM V	IF(AV)		IFSM A (60Hz)	I <sup>2</sup> t A <sup>2</sup> s	VFM V (25°C)	IRRM mA (125°C)	trr ns	Rthj-c °C / W	Fig No.
		A	°C							
DCA100AA60	600	100	85	2000	16700	1.3	100	300	0.5	3
DCA150AA60	600	150	72	2500	26000	1.3	150	300	0.4	3
DCA100BA60	600	100	80	1350	7500	1.55	100	200	0.45	3
DCA150BA65	650	150	63	1500	9300	1.7	150	200	0.34	3
DKA200AA60	600	100	85	2000	16700	1.3	100	300	0.5	3
DKA300AA60	600	150	72	2500	26000	1.3	150	300	0.4	3
DSR200BA60	600	200	85	3300	45000	1.3	200	300	0.25	13
DBA200UA40	400	100	96	700	2100	1.20	100(150°C)	130	0.45	23
DBA200UA60	600	100	89	700	2100	1.35	100(150°C)	250	0.45	23
DBA200WA40	400	100	96	1100	5050	1.2	4	110	0.45	23
DBA200WA60	600	100	89	1100	5050	1.5	4	130	0.45	23





## FAST RECOVERY DIODE

Viso : 2500V (RMS) Tj(max) : 150°C

Type	VRRM V	IF(AV)		IFSM A (60Hz)	I <sup>2</sup> t A <sup>2</sup> s	VFM V (25°C)	IRRM mA (125°C)	trr ns	Rthj-c °C / W	Fig No.
		A	°C							
FD25CA120	1200	25	114	400	660	1.8	2(150°C)	200	0.4	6
FD60BA60	600	60	80	600	1490	1.6	60	100	0.36	6
FRD100CA120	1200	100	78	2000	16600	1.8	5(150°C)	300	0.4	3
FDS100CA120	1200	100	78	2000	16600	1.8	5(150°C)	300	0.4	3
FRS150BA50	500	150	85	3000	37500	1.3	150	200	0.33	7
FRS200CA120	1200	200	78	3300	45000	1.8	10(150°C)	350	0.2	13
FRS300BA50	500	300	85	4000	66600	1.3	300	200	0.165	7
FRS300CA50	500	300	116	4000	66600	1.3	300	200	0.085	7
FRS400BA60	600	400	94	4000	66640	1.3	400	200	0.1	8
FRS400CA120	1200	400	78	4000	66640	1.8	20(150°C)	400	0.1	8
FRS400EA200	2000	400	79	5000	104000	2.2(125°C)	100(150°C)	700	0.08	8
DKR200AB60	600	100	133	3600	54000	1.4	100	200	0.125*	16
DKR300AB60	600	150	124	3600	54000	1.4	100	200	0.125*	16
DKR400AB60	600	200	122	6000	150000	1.4	150	200	0.1*	16

\*NON-ISO Type




## SHOTTKY BARRIER DIODE

Viso : 2500V (RMS) Tj(max) : 150°C

Type	VRRM V	IF(AV)		IFSM A (60Hz)	I <sup>2</sup> t A <sup>2</sup> s	VFM V (25°C)	IRRM mA (125°C)	Rthj-c °C / W	Fig No.
		A	°C						
BKR400ABZ50	50	200	121	7600	240000	0.57	2000	0.2*	16
BKR400AB10	100	200	112	3620	54450	0.93	40	0.2*	16
BKA400AA10	100	200	83	3620	54450	0.82	140	0.4	1



\*NON-ISO Type



## RECTIFIER DIODE DD/KD SERIES

Viso : 2500V (RMS) Tj(max) : 150°C


Type	VRRM V	IF(AV)		IFSM A (60Hz)	I <sup>2</sup> t A <sup>2</sup> s	VFM V (25°C)	IRRM mA (150°C)	Rthj-c °C / W	Fig No.
		A	°C						
DD60KB80/160	800, 1600	60	110	1200	6000	1.35	20	0.52	3
KD60GB80	800	60	114	1200	6000	1.25	20	0.5	3
KD60HB160	1600	60	111	1200	6000	1.35	20	0.5	3
DKA60KB80/160	800, 1600	60	110	1200	6000	1.35	20	0.52	3
DD100KB80/160	800, 1600	100	105	2000	16500	1.35	30	0.35	3
DD160KB80/160	800, 1600	160	90	3200	42600	1.35	30	0.3	3
KD160KB80/160	800, 1600	160	90	3200	42600	1.35	30	0.3	3
DD200KB80/160	800, 1600	200	106	5500	125000	1.3	50	0.17	18
DD200KB220	2200	200	105	5500	125000	1.4	50	0.17	18
DD240KB80/160	800, 1600	240	95	5500	125000	1.35	50	0.17	18
DD300KB80/160	800, 1600	300	91	6000	150000	1.5	50	0.14	4



## 3-PHASE DIODE DF-NA SERIES

Viso : 2500V (RMS) Tj(max) : 150°C


Type	VRRM V	ID		IFSM A (60Hz)	I <sup>2</sup> t A <sup>2</sup> s	VFM V (25°C)	IRRM mA (150°C)	Rthj-c °C / W	Fig No.
		A	°C						
DF20NA80/160 S	800, 1600	20	111	350	500	1.2	4/8	0.8	24
DF20NA80/160 F1	800, 1600	20	111	350	500	1.2	4/8	0.8	25
DF30NA80/160 S	800, 1600	30	92	400	660	1.2	5/14	0.8	24
DF30NA80/160 F1	800, 1600	30	92	400	660	1.2	5/14	0.8	25



### 3-PHASE DIODE DF-AC SERIES

Viso : 2500V (RMS) Tj(max) : 150°C


Type	VRRM V	ID		IFSM A (60Hz)	I <sup>2</sup> t A <sup>2</sup> s	VFM V (25°C)	IRRM mA (150°C)	Rthj-c °C / W	Fig No.
		A	°C						
DF75AC80/160	800, 1600	75	100	1000	4100	1.4	10	0.24	26
DF100AC80/160	800, 1600	100	102	1300	7000	1.2	15	0.2	26
DF150AC80/160	800, 1600	150	106	2000	17000	1.2	15	0.12	27
DF200AC80/160	800, 1600	200	106	2500	26000	1.2	20	0.09	27



### 3-PHASE DIODE DF-AA/BA/CA SERIES

Viso : 2500V (RMS) Tj(max) : 150°C


Type	VRRM V	ID		IFSM A (60Hz)	VFM V (25°C)	IRRM mA (150°C)	Rthj-c °C / W	Fig No.
		A	°C					
DF20CA80/160	800, 1600	20	123	600	1.1	8	0.6	5
DF20AA120/160	1200, 1600	20	119	240	1.25	3	0.6	5
DF30CA80/160	800, 1600	30	122	850	1.1	8	0.42	5
DF30AA120/160	1200, 1600	30	117	300	1.3	3	0.42	5
DF40BA80	800	40	119	700	1.2	4	0.32	6
DF40AA120/160	1200, 1600	40	117	700	1.3	3	0.32	6
DF50BA80	800	50	114	700	1.2	4	0.30	9
DF50AA120/160	1200, 1600	50	114	700	1.2	8	0.30	9
DF60BA80	800	60	115	1000	1.2	6	0.24	6
DF60AA120/160	1200, 1600	60	112	1000	1.3	12	0.24	6
DF75BA80	800	75	107	1000	1.2	10	0.24	9
DF75AA120/160	1200, 1600	75	100	1000	1.4	10	0.24	9
DF100BA80	800	100	102	1000	1.2	15	0.2	9
DF100AA120/160	1200, 1600	100	102	1000	1.2	15	0.2	9
DF150AB80/160	800, 1600	150	100	1200	1.2	15	0.14	10
DF200AB80/160	800, 1600	200	102	2000	1.2	20	0.1	10




### 3-PHASE DIODE DF-LA/LB SERIES

Viso : 2500V (RMS) Tj(max) : 150°C

Type	VRRM V	ID		IFSM A (60Hz)	VFM V (25°C)	IRRM mA (150°C)	Rthj-c °C / W	Fig No.
		A	°C					
DF60LA80/160	800, 1600	60	111	800	1.3	8	0.25	19
DF60LB80/160	800, 1600	60	111	800	1.3	8	0.25	20
DF75LA80/160	800, 1600	75	101	1000	1.3	8	0.25	19
DF75LB80/160	800, 1600	75	101	1000	1.3	8	0.25	20
DF100LA80/160	800, 1600	100	90	1300	1.3	12	0.23	19
DF100LB80/160	800, 1600	100	90	1300	1.3	12	0.23	20



Connections




### 3-PHASE DIODE + THYRISTOR DFA SERIES

Viso : 2500V (RMS)

Type	VDRM / VRRM V	IF(AV)		IFSM A (60Hz)	I <sup>2</sup> t A <sup>2</sup> s	VFM(D) V (25°C)	IRRM(D) mA (150°C)	Rthj-c(D) °C / W	VTM(THY) V (25°C)	IDRM(THY) mA (135°C)	Rthj-c(THY) °C / W	Tj(max)		Fig No.
		A	°C									(thy)	(Diode)	
DFA50BA80/160	800, 1600	50	117	800	2660	1.30	8	0.25	1.25	50	0.80	135°C	150°C	15
DFA75BA80/160	800, 1600	75	101	1000	4150	1.30	8	0.25	1.20	60	0.40	135°C	150°C	15
DFA100BA80/160	800, 1600	100	98	1300	7030	1.30	12	0.20	1.20	70	0.36	135°C	150°C	15
DFA150BA80/160	800, 1600	150	105	1600	10670	1.35	15	0.09	1.35	100	0.22	150°C	150°C	15
DFA150AA80/160	800, 1600	150	93	1600	10670	1.35	15	0.14	1.35	100	0.21	135°C	150°C	28
DFA200AA80/160	800, 1600	200	96	2000	17000	1.35	20	0.1	1.15	50	0.18	135°C	150°C	28
DFA150CB80/160	800, 1600	150	113	1600	10670	1.35	15	0.09	1.35	100	0.18	150°C	150°C	17
DFA200CB80/160	800, 1600	200	96	2000	17000	1.35	20	0.1	1.15	50	0.15	150°C	150°C	17

Connections



Package




## THYRISTOR


### THYRISTOR AK SERIES

Viso : 2500V (RMS) dv/dt : 500V/μs Tj(max) : 125°C

Type	VDRM / VRRM V	IT(AV)		IT(RMS)		ITSM A (60Hz)	I <sup>2</sup> t A <sup>2</sup> s	IGT mA (25°C)	VGT V (25°C)	VTM V (25°C)	IDRM/IRRM mA (125°C)	Rthj-c °C / W	Fig No.
		A	°C	A	°C								
AK25GB80	400, 800	25	97	55	97	500	1000	50	3	1.5	8	0.8	13
AK25HB160	1200, 1600	25	94	55	94	500	1000	50	2	1.6	8	0.8	13
AK55GB80	400, 800	55	89	122	89	1100	5000	100	3	1.35	20	0.5	13
AK55HB160	1200, 1600	55	85	122	85	1100	5000	100	2	1.5	20	0.5	13
AK90GB80	400, 800	90	91	200	91	1800	15000	100	3	1.3	30	0.3	13
AK90HB160	1200, 1600	90	88	200	88	1800	15000	100	2	1.4	30	0.3	13



Connections







### HIGH CURRENT THYRISTOR

Viso : 2500V (RMS) dv/dt : 500V/ $\mu$ s Tj (max) : 125°C

Type	VDRM / VRRM V	IT(AV)		ITSM A (60Hz)	I <sup>2</sup> t A <sup>2</sup> s	IGT mA (25°C)	VGT V (25°C)	VTM V (25°C)	IDRM/IRRM mA (125°C)	Rthj-c °C/W	Fig No.
		A	°C								
SBA500AA80/160	800, 1600	500	66	10000	4.16 × 10 <sup>5</sup>	200	3	1.45	150	0.085	14
SBB500AA80/160	800, 1600	500	66	10000	4.16 × 10 <sup>5</sup>	200	3	1.45	150	0.085	14
SSA500AA80/160	800, 1600	500	66	10000	4.16 × 10 <sup>5</sup>	200	3	1.45	150	0.085	22




Connections



### THYRISTOR PK/PD SERIES

Viso : 2500V (RMS) dv/dt : 500V/ $\mu$ s Tj (max) : 125°C

Type	VDRM / VRRM V	IT(AV)		ITSM A (60Hz)	I <sup>2</sup> t A <sup>2</sup> s	IGT mA (25°C)	VGT V (25°C)	VTM V (25°C)	IDRM/IRRM mA (125°C)	Rthj-c °C/W	Fig No.
		A	°C								
PK25FG80/160	800, 1600	25	81	700	2870	50	3	1.6	5	1.1	2
PD25FG80/160	800, 1600	25	81	700	2870	50	3	1.6	5	1.1	2
PK40FG80/160	800, 1600	40	83	950	3760	50	3	1.6	10	0.65	2
PD40FG80/160	800, 1600	40	83	950	3760	50	3	1.6	10	0.65	2
PK55FG80/160	800, 1600	55	81	1300	7040	50	3	1.6	15	0.5	2
PD55FG80/160	800, 1600	55	81	1300	7040	50	3	1.6	15	0.5	2
PK70FG80/160	800, 1600	70	84	1600	10660	50	3	1.6	20	0.37	2
PD70FG80/160	800, 1600	70	84	1600	10660	50	3	1.6	20	0.37	2
PK90FG80/160	800, 1600	90	82	2300	22040	50	3	1.6	25	0.3	2
PD90FG80/160	800, 1600	90	82	2300	22040	50	3	1.6	25	0.3	2
PK110FG80/160	800, 1600	110	81	3000	37500	50	3	1.6	30	0.25	2
PD110FG80/160	800, 1600	110	81	3000	37500	50	3	1.6	30	0.25	2
PK130FG80/160	800, 1600	130	83	3500	51040	50	3	1.6	35	0.2	2
PD130FG80/160	800, 1600	130	83	3500	51040	50	3	1.6	35	0.2	2
PK160FG80/160	800, 1600	160	84	5400	125000	100	3	1.5	100	0.18	21
PD160FG80/160	800, 1600	160	84	5400	125000	100	3	1.5	100	0.18	21
PK200FG80/160	800, 1600	200	73	6500	180000	100	3	1.5	100	0.167	21
PD200FG80/160	800, 1600	200	73	6500	180000	100	3	1.5	100	0.167	21
PK250GB80/HB160	800, 1600	250	72	5500	125000	100	3	1.6	50	0.14	4
PD250GB80/HB160	800, 1600	250	72	5500	125000	100	3	1.6	50	0.14	4




Connections



### THYRISTOR SCA/SCE SERIES

Viso : 2500V (RMS) dv/dt : 500V/ $\mu$ s

Type	VDRM / VRRM V	IT(AV)		ITSM A (60Hz)	I <sup>2</sup> t A <sup>2</sup> s	IGT mA (25°C)	VGT V (25°C)	VTM V (25°C)	IDRM/IRRM mA	Rthj-c °C/W	Tj(max) °C	Fig No.
		A	°C									
SCA55AA160	1600	55	95	1500	9380	100	2.5	1.65	20(130°C)	0.4	130	30
SCE55AA160	1600	55	95	1500	9380	100	2.5	1.65	20(130°C)	0.4	130	30
SCA70AA160	1600	70	101	1750	12800	100	2.5	1.7	20(130°C)	0.25	130	30
SCE70AA160	1600	70	101	1750	12800	100	2.5	1.7	20(130°C)	0.25	130	30
SCA90AA160	1600	90	100	2300	22040	100	2.5	1.7	20(130°C)	0.2	130	30
SCE90AA160	1600	90	100	2300	22040	100	2.5	1.7	20(130°C)	0.2	130	30
SCA110AA160	1600	110	95	2500	25000	100	2.5	1.7	20(130°C)	0.19	130	30
SCE110AA160	1600	110	95	2500	25000	100	2.5	1.7	20(130°C)	0.19	130	30
SCA130AA80/160/180	800, 1600, 1800	130	92	5400	125000	100	3	1.5	100(125°C)	0.18	125	29
SCE130AA80/160/180	800, 1600, 1800	130	92	5400	125000	100	3	1.5	100(125°C)	0.18	125	29
SCA160AA80/160/180	800, 1600, 1800	160	88	5900	145000	100	3	1.4	100(125°C)	0.17	125	29
SCE160AA80/160/180	800, 1600, 1800	160	88	5900	145000	100	3	1.4	100(125°C)	0.17	125	29
SCA200AA80/160/180	800, 1600, 1800	200	82	6500	180000	100	3	1.4	150(125°C)	0.155	125	29
SCE200AA80/160/180	800, 1600, 1800	200	82	6500	180000	100	3	1.4	150(125°C)	0.155	125	29
SCA160BA160	1600	160	102	4500	104000	100	3	1.65	100(150°C)	0.17	150	29
SCE160BA160	1600	160	102	4500	104000	100	3	1.65	100(150°C)	0.17	150	29
SCA200BA160	1600	200	95	5500	126000	100	3	1.68	120(150°C)	0.155	150	29
SCE200BA160	1600	200	95	5500	126000	100	3	1.68	120(150°C)	0.155	150	29




Connections




### THYRISTOR PWB SERIES

NON-ISO di/dt : 50A/ $\mu$ s, VGT : 2V (25°C), Tj (max) : 150°C

Type	VDRM / VRRM V	IT(AV)		IT(RMS)		ITSM A (60Hz)	I <sup>2</sup> t A <sup>2</sup> s	dv/dt V/ $\mu$ s(150°C)	IGT mA (25°C)	VTM V (25°C)	IDRM/IRRM mA (150°C)	Rthj-c °C/W	Fig No.
		A	°C	A	°C								
PWB60A30/40	300, 400	60	123	94	123	1800	13500	50	150	1.25	10	0.35	11
PWB80A30/40	300, 400	80	116	125	116	2500	26000	50	150	1.2	12	0.35	11
PWB100A30/40	300, 400	100	114	157	114	3500	51000	50	150	1.2	15	0.3	11
PWB130A30/40	300, 400	130	112	204	112	3500	51000	50	150	1.2	30	0.20	11
PWB150AA30/40	300, 400	150	121	230	121	3500	51000	200	100	1.2	40	0.15	12
PWB200AA30/40	300, 400	200	121	314	121	6000	149940	200	150	1.2	60	0.12	12




Connections





# DISCRETE



## PRODUCT FEATURES

- ▶ **Broad Product Line up**  
- Easy to choose a suitable Device -

**Through Hole type : 7packages**  
TO-92, TO-251, TO-220AB, TO-220AB-2L,  
TO-220F, TO-3P, TO-3PF

**Surface Mount type : 3packages**  
SOT-89, TO-252, TO-263

**Tab terminal type : 1package**  
TO-3

- ▶ **Triac - Qseries : Tjmax=150°C only**

Easy to design with smaller or no heat sinks. It will reduce the total cost.

- ▶ **Triac / Thyristor - The following high sensitivity models are available**

- ▶ **RoHS Compliance**

All products are RoHS-compliant.

- ▶ **Triac - Available up to 800V**

- ▶ **Low loss (V<sub>T</sub>=1.4V) models are available**

Based on SanRex's new diffusion technology, we achieve a very low On-State Voltage and high blocking voltage.

Triac	Standard		Sensitive Gate	
	I <sup>+</sup> , I <sup>-</sup> , III <sup>-</sup>	III <sup>+</sup>	I <sup>+</sup> , I <sup>-</sup> , III <sup>-</sup>	III <sup>+</sup>
TMG1C <sub>-</sub>			5	10
TMG2C <sub>-</sub>	15	—		
TMG2D <sub>-</sub>			5	10
TMG3C <sub>-</sub>	15	—		
TMG3D <sub>-</sub>			5	10
TMG5C <sub>-</sub>	20	—		
TMG8/12/16/20/25C <sub>-</sub>	30	—		
TMG5/8/12/16/20/25D <sub>-</sub>			10	—
TMG40/C <sub>-</sub>	50	—		

(mA)


Thyristor	Standard	Sensitive Gate
	SMG04/05/08C <sub>-</sub>	
SMG2D <sub>-</sub>		0.2
SMG5/8C <sub>-</sub>	10	
SMG3D <sub>-</sub>		0.2
SMG12/16C <sub>-</sub>	30	
SMG5F <sub>-</sub>		0.2

(mA)


It will be suitable for Logic Level triggering

## TYPE DESIGNATION

### TMG/SMG SERIES



### OTHER DISCRETE SERIES



# TRIAC

## Through Hole / Standard

Package	Type	V <sub>DRM</sub> V	I <sub>T</sub> (RMS) A	I <sub>DRM</sub> mA	V <sub>TM</sub> V	I <sub>GT</sub> mA		V <sub>GT</sub> V		T <sub>j</sub> °C	[dv/dt] <sub>c</sub>		R <sub>thj-c</sub> °C/W	Fig No.
						I+,I-,II-	III +	I+,I-,II-	III +		V/μs (T <sub>j</sub> =125°C)	-A/ms [-di/dt] <sub>c</sub>		
TO-251	TMG2C60/80C	600, 800	2	1	1.6	15	—	1.5	—	125	3	1	5.8	D2
	TMG3C60/80C	600, 800	3	1	1.4	15	—	1.5	—	125	5	1.5	3.8	
	TMG5C60C	600	5	1	1.4	20	—	1.5	—	125	5	2.5	3	
TO-220AB	TMG5C60	600	5	1	1.4	20	—	1.5	—	125	5	2.5	3	D3
	TMG8C60	600	8	2	1.4	30	—	1.5	—	125	10	4	2	
	TMG12C60/80	600, 800	12	2	1.4	30	—	1.5	—	125	10	6	1.8	
	TMG16C60	600	16	2	1.4	30	—	1.5	—	125	10	8	1.4	
TO-220AB2	TMG20C60	600	20	2	1.4	30	—	1.5	—	125	10	8	1.1	D5
TO-220F	TMG2C60F	600	2	1	1.6	15	—	1.5	—	125	3	1	7.5	*D6
	TMG3C60F	600	3	1	1.4	15	—	1.5	—	125	5	1.5	5	
	TMG5C60F	600	5	1	1.4	20	—	1.5	—	125	5	2.5	4	
	TMG8C60/80F	600, 800	8	2	1.4	30	—	1.5	—	125	10	4	3.7	
	TMG12C60/80F	600, 800	12	2	1.4	30	—	1.5	—	125	10	6	3.3	
	TMG16C60/80F	600, 800	16	2	1.4	30	—	1.5	—	125	10	8	3	
	TMG20C60/80F	600, 800	20	2	1.4	30	—	1.5	—	125	10	8	2.5	
	TMG25C60/80F	600, 800	25	5	1.4	30	—	1.5	—	125	10	12.5	2.2	
TO-3P	TMG25C60/80L	600, 800	25	5	1.4	30	—	1.5	—	125	10	12.5	1.2	D7
	TMG40C60/80L	600, 800	40	5	1.4	50	—	1.5	—	125	10	20	0.6	
TO-3PF	TMG25C60/80J	600, 800	25	5	1.4	30	—	1.5	—	125	10	12.5	1.4	*D8
	TMG40C60/80J	600, 800	40	5	1.4	50	—	1.5	—	125	10	20	1.1	

\*UL File No.E76102

## Through Hole / Sensitive Gate

Package	Type	V <sub>DRM</sub> V	I <sub>T</sub> (RMS) A	I <sub>DRM</sub> mA	V <sub>TM</sub> V	I <sub>GT</sub> mA		V <sub>GT</sub> V		T <sub>j</sub> °C	[dv/dt] <sub>c</sub>		R <sub>thj-c</sub> °C/W	Fig No.
						I+,I-,II-	III +	I+,I-,II-	III +		V/μs (T <sub>j</sub> =125°C)	-A/ms [-di/dt] <sub>c</sub>		
TO-92	TMG1C60/80	600, 800	1	0.5	1.6	5	10	1.8	2	125	2	0.5	**120	D1
TO-251	TMG2D60/80C	600, 800	2	1	1.6	5	10	1.5	2	125	3	1	5.8	D2
	TMG3D60/80C	600, 800	3	1	1.4	5	10	1.5	2	125	5	1.5	3.8	
	TMG5D60/80C	600, 800	5	1	1.4	10	—	1.5	—	125	5	2.5	3	
TO-220AB	TMG12D60	600	12	2	1.4	10	—	1.5	—	125	10	6	1.8	D3
	TMG16D80	800	16	2	1.4	10	—	1.5	—	125	10	8	1.4	
TO-220AB2	TMG20D60/80	600, 800	20	2	1.4	10	—	1.5	—	125	10	8	1.1	D5
TO-220F	TMG2D60/80F	600, 800	2	1	1.6	5	10	1.5	2	125	3	1	7.5	*D6
	TMG3D60/80F	600, 800	3	1	1.4	5	10	1.5	2	125	5	1.5	5	
	TMG5D80F	800	5	1	1.4	10	—	1.5	—	125	5	2.5	4	
	TMG8D60/80F	600, 800	8	2	1.4	10	—	1.5	—	125	10	4	3.7	
	TMG12D60/80F	600, 800	12	2	1.4	10	—	1.5	—	125	10	6	3.3	
	TMG16D60F	600	16	2	1.4	10	—	1.5	—	125	10	8	3	
	TMG20D60F	600	20	2	1.4	10	—	1.5	—	125	10	8	2.5	
	TMG25D60F	600	25	5	1.4	10	—	1.5	—	125	10	12.5	2.2	

\*UL File No.E76102 \*\*R<sub>th</sub>(j-a)

## Through Hole / T<sub>j</sub>=150°C

Package	Type	V <sub>DRM</sub> V	I <sub>T</sub> (RMS) A	I <sub>DRM</sub> mA	V <sub>TM</sub> V	I <sub>GT</sub> mA		V <sub>GT</sub> V		T <sub>j</sub> °C	[dv/dt] <sub>c</sub>		R <sub>thj-c</sub> °C/W	Fig No.
						I+,I-,II-	III +	I+,I-,II-	III +		V/μs (T <sub>j</sub> =150°C)	-A/ms [-di/dt] <sub>c</sub>		
TO-251	TMG5CQ60C	600	5	2	1.4	15	—	1.5	—	150	2	2.5	3	D2
TO-220AB	TMG8CQ60	600	8	2	1.4	30	—	1.5	—	150	5	4	2	D3
	TMG16CQ60	600	16	2	1.4	30	—	1.5	—	150	5	8	1.4	
TO-220AB2	TMG20CQ60	600	20	3	1.4	30	—	1.5	—	150	5	10	1.1	D5
TO-220F	TMG2DQ60F	600	2	1	1.6	5	10	1.5	—	150	1	1	7.5	*D6
	TMG3CQ60F	600	3	2	1.4	15	—	1.5	2	150	1	1.5	5	
	TMG5CQ60F	600	5	2	1.4	20	—	1.5	—	150	2	2.5	4	
	TMG8CQ60F	600	8	2	1.4	30	—	1.5	—	150	5	4	3.7	
	TMG12CQ60F	600	12	2	1.4	30	—	1.5	—	150	5	6	3.3	
	TMG16CQ60F	600	16	3	1.4	30	—	1.5	—	150	5	8	3	
	TMG20CQ60F	600	20	3	1.4	30	—	1.5	—	150	5	10	2.5	
	TMG25CQ60F	600	25	5	1.4	30	—	1.5	—	150	5	12.5	2.2	
TO-3P	TMG25CQ60L	600	25	5	1.4	30	—	1.5	—	150	5	12.5	1.2	D7
	TMG40CQ60L	600	40	8	1.4	50	—	1.5	—	150	5	20	0.6	
TO-3PF	TMG25CQ60J	600	25	5	1.4	30	—	1.5	—	150	5	12.5	1.4	*D8
	TMG40CQ60J	600	40	8	1.4	50	—	1.5	—	150	5	20	1.1	

\*UL File No.E76102

### SMD (Surface Mount Device) / Standard

Package	Type	V <sub>DRM</sub> V	I <sub>T(RMS)</sub> A	I <sub>DRM</sub> mA	V <sub>TM</sub> V	I <sub>GT</sub> mA		V <sub>GT</sub> V		T <sub>j</sub> °C	[dv/dt]c		R <sub>thj-c</sub> °C/W	Fig No.
						I+,I-,II-	III +	I+,I-,II-	III +		V/μs (T <sub>j</sub> =125°C)	-A/ms [-di/dt]c		
TO-252 (D pak)	TMG2C60D	600	2	1	1.6	15	—	1.5	2	125	3	1	5.8	D10
	TMG3C60D	600	3	1	1.4	15	—	1.5	—	125	5	1.5	3.8	
	TMG5C60D	600	5	1	1.4	20	—	1.5	—	125	5	2.5	3	
TO-263 (D2 pak)	TMG5C60H	600	5	1	1.4	20	—	1.5	—	125	5	2.5	3	D11
	TMG8C60H	600	8	2	1.4	30	—	1.5	—	125	10	4	2	
	TMG16C60H	600	16	2	1.4	30	—	1.5	—	125	10	8	1.4	

### SMD (Surface Mount Device) / Sensitive Gate

Package	Type	V <sub>DRM</sub> V	I <sub>T(RMS)</sub> A	I <sub>DRM</sub> mA	V <sub>TM</sub> V	I <sub>GT</sub> mA		V <sub>GT</sub> V		T <sub>j</sub> °C	[dv/dt]c		R <sub>thj-c</sub> °C/W	Fig No.
						I+,I-,II-	III +	I+,I-,II-	III +		V/μs (T <sub>j</sub> =125°C)	-A/ms [-di/dt]c		
SOT-89	TMG1C60A	600	1	0.5	1.6	5	10	1.8	2	125	2	0.5	** 65	D9
TO-252 (D pak)	TMG3D60D	600	3	1	1.4	5	10	1.5	2	125	5	1.5	3.8	D10
	TMG5D60D	600	5	1	1.4	10	—	1.5	—	125	5	2.5	3	

\*\* R<sub>th(j-a)</sub>

### SMD (Surface Mount Device) / T<sub>j</sub>=150°C

Package	Type	V <sub>DRM</sub> V	I <sub>T(RMS)</sub> A	I <sub>DRM</sub> mA	V <sub>TM</sub> V	I <sub>GT</sub> mA		V <sub>GT</sub> V		T <sub>j</sub> °C	[dv/dt]c		R <sub>thj-c</sub> °C/W	Fig No.
						I+,I-,II-	III +	I+,I-,II-	III +		V/μs (T <sub>j</sub> =125°C)	-A/ms [-di/dt]c		
SOT-89	TMG1CQ60A	600	1	1	1.6	5	10	1.8	2	150	1	0.5	** 65	D9
TO-252 (D pak)	TMG3CQ60D	600	3	2	1.4	15	—	1.5	—	150	1	1.5	3.8	D10
	TMG3DQ60D	600	3	2	1.4	5	10	1.5	2	150	1	1.5	3.8	
	TMG5CQ60D	600	5	2	1.4	20	—	1.5	—	150	2	2.5	3	

\*\* R<sub>th(j-a)</sub>

### Tab terminal / Standard

Package	Type	V <sub>DRM</sub> V	I <sub>T(RMS)</sub> A	I <sub>DRM</sub> mA	V <sub>TM</sub> V	I <sub>GT</sub> mA		V <sub>GT</sub> V		T <sub>j</sub> °C	[dv/dt]c		R <sub>thj-c</sub> °C/W	Fig No.
						I+,I-,II-	III +	I+,I-,II-	III +		V/μs (T <sub>j</sub> =125°C)	-A/ms [-di/dt]c		
TO-3	TG16C40/60	400, 600	16	3	1.5	50	—	3	—	125	6	8	2	* D12
	TG25C40/60	400, 600	25	5	1.4	50	—	3	—	125	6	15	1.6	
	TG35C40/60	400, 600	35	5	1.4	50	—	3	—	125	5	15	1.5	
	TG40C60	600	40	5	1.4	50	—	1.5	—	125	6	10	1.3	
not standard	TG70AA40/60	400, 600	70	10	1.35	50	—	3	—	125	6	8	0.83	D14

\* UL File No.E76102

## THYRISTOR

### Through Hole / Standard

Package	Type	V <sub>DRM</sub> V	I <sub>T(AV)</sub> A	I <sub>T(RMS)</sub> A	I <sub>DRM</sub> mA	V <sub>TM</sub> V	I <sub>GT</sub> mA	V <sub>GT</sub> V	T <sub>j</sub> °C	R <sub>thj-c</sub> °C/W	Fig No.
TO-220AB	SMG8C60	600	8	13.0	2	1.5	10	1.4	125	2	D3
	SMG12C60	600	12	19.0	2	1.5	30	1.4	125	1.8	
	SMG16C60	600	16	25.0	2	1.5	30	1.4	125	1.4	
TO-220F	SMG5C60F	600	5	7.8	2	1.5	10	1.4	125	4	* D6
	SMG8C60F	600	8	13.0	2	1.5	10	1.4	125	3.7	
	SMG12C60F	600	12	19.0	2	1.5	30	1.4	125	3.3	
	SMG16C60F	600	16	25.0	2	1.5	30	1.4	125	3	

\* UL File No.E76102

### Through Hole / Sensitive Gate

Package	Type	V <sub>DRM</sub> V	I <sub>T(AV)</sub> A	I <sub>T(RMS)</sub> A	I <sub>DRM</sub> mA	V <sub>TM</sub> V	I <sub>GT</sub> mA	V <sub>GT</sub> V	T <sub>j</sub> °C	R <sub>thj-c</sub> °C/W	Fig No.
TO-92	SMG04C60	600	0.4	0.63	0.5	1.2	0.1	0.8	125	** 150	D1
	SMG05C60	600	0.5	0.78	0.5	1.2	0.1	0.8	125	** 150	
TO-251	SMG3D60C	600	3	4.7	1	1.5	0.2	0.8	125	3.8	D2

\*\* R<sub>th(j-a)</sub>

### SMD (Surface Mount Device) / Standard

Package	Type	V <sub>DRM</sub> V	I <sub>T(AV)</sub> A	I <sub>T(RMS)</sub> A	I <sub>DRM</sub> mA	V <sub>TM</sub> V	I <sub>GT</sub> mA	V <sub>GT</sub> V	T <sub>j</sub> °C	R <sub>thj-c</sub> °C/W	Fig No.
TO-252 (D pak)	SMG5C60D	600	5	7.8	2	1.8	10	0.8	125	3	D10
TO-263 (D2 pak)	SMG5C60H	600	5	7.8	2	1.5	10	1.4	125	3	D11

### SMD (Surface Mount Device) / Sensitive Gate

Package	Type	V <sub>DRM</sub> V	I <sub>T(AV)</sub> A	I <sub>T(RMS)</sub> A	I <sub>DRM</sub> mA	V <sub>TM</sub> V	I <sub>GT</sub> mA	V <sub>GT</sub> V	T <sub>j</sub> °C	R <sub>thj-c</sub> °C/W	Fig No.
SOT-89	SMG05C60A	600	0.5	0.78	0.5	1.9	0.1	0.8	125	**70	D9
	SMG08C60A	600	0.8	1.3	0.5	1.5	0.1	0.8	125	**65	
TO-252 (D pak)	SMG3D60D	600	3	4.7	1	1.5	0.2	0.8	125	3.8	D10
	SMG5F60D	600	5	7.8	2	1.8	0.2	0.8	125	3	

\*\*R<sub>th(j-a)</sub>

### Tab terminal / Standard

Package	Type	V <sub>DRM</sub> V	I <sub>T(AV)</sub> A	I <sub>T(RMS)</sub> A	I <sub>DRM</sub> mA	V <sub>TM</sub> V	I <sub>GT</sub> mA	V <sub>GT</sub> V	T <sub>j</sub> °C	R <sub>thj-c</sub> °C/W	Fig No.
TO-3	SG16AA40/60	400, 600	16	25	3	1.5	40	3	125	2	*D12
	SG25AA40/60	400, 600	25	39	5	1.4	40	3	125	1.6	

\*UL File No.E76102

## FRD

### Tab terminal

Package	Type	V <sub>RRM</sub> V	I <sub>F(AV)</sub>		I <sub>FSM</sub> A (60Hz)	I <sub>t</sub> <sup>2</sup> A <sup>2</sup> s	V <sub>FM</sub> V (25°C)	I <sub>RRM</sub> mA (125°C)	tr <sub>ns</sub>	R <sub>thj-c</sub> °C/W	Fig No.
			A	°C							
TO-3	FRG25BA60	600	25	94	450	840	1.3	30 (150°C)	100	1.6	D13
	FRG25CA120	1200	25	78	400	660	1.8	1 (150°C)	200	1.6	

## DIODE

### Through Hole

Package	Type	V <sub>RRM</sub> V	I <sub>F(AV)</sub> A	I <sub>FSM</sub> A (60Hz)	I <sub>t</sub> <sup>2</sup> A <sup>2</sup> s	V <sub>FM</sub> V (25°C)	I <sub>RRM</sub> mA (125°C)	T <sub>j</sub> °C	R <sub>thj-c</sub> °C/W	Fig No.
TO-220AB-2L	DMG35AA100	1000	35	300	380	1.2	100	180	1	D4

### Tab terminal

Package	Type	V <sub>RRM</sub> V	I <sub>F(AV)</sub>		I <sub>FSM</sub> A (60Hz)	I <sub>t</sub> <sup>2</sup> A <sup>2</sup> s	V <sub>FM</sub> V (25°C)	I <sub>RRM</sub> mA (150°C)	R <sub>thj-c</sub> °C/W	Fig No.
			A	°C						
TO-3	DG20AA80/160	800, 1600	20	101	450	840	1.65	8	1.6	D13

# OUTLINE DRAWINGS

## POWER MODULE

(m/m)

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7





Fig. 8














Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23





Fig. 24






Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29





Fig. 30



Please refer specification for details



Fig.  
D1




Fig.  
D2




Fig.  
D3




Fig.  
D4




Fig.  
D5




Fig.  
D6




Fig.  
D7




Fig.  
D8






Fig. D9




Recommended Mounting Pad

Fig. D10



Recommended Mounting Pad

Fig. D11



Recommended Mounting Pad

Fig. D12




Fig. D13





Fig. D14




Please refer specification for details

# PACKAGING SPECIFICATIONS


## Through Hole

### TO-92 (Taping)




P0 : Cumulative Feedhole Pitch ±1.0/20pitch


Inner Box  
3,000pcs/Box  
(Corrugated Board)




Outer Box  
5 Packing Boxes (15,000pcs)/Box  
(Corrugated Board)




### TO-92 (Formed Lead)



Box (White paperboard)  
500 pcs/Box




Inner Box (White paperboard)  
4 Boxes (2,000pcs) per Inner Box




Outer Box (Corrugated Board)  
5 Inner boxes (10,000pcs)  
per Outer Box


### TO-92 (Straight Lead)



Bag (Polyethylene)  
200 pcs per Bag




Inner Box (White paperboard)  
10Bags (2,000pcs) per Inner Box




Outer Box (Corrugated Board)  
5 Inner boxes (10,000pcs)  
per Outer Box

### TO-251



Note) A label with Type and Quantity is indicated on the Outer box.


### TO-220AB / TO-220AB-2L



Note) A label with Type and Quantity is indicated on the Outer box.




**TO-220F (Straight Lead)**




Note) A label with Type and Quantity is indicated on the Outer box.

**TO-220F (Formed Lead)**




Note) A label with Type and Quantity is indicated on the Outer box.

**TO-3P / TO-3PF**




Note) A label with Type and Quantity is indicated on the Outer box.




# SMD (Surface Mount Device)

## SOT-89


SOT-89 Reel Outline



Dimensions are in millimeter				
Tape Size	A	B	C	W
12mm	180 $\pm$ 1.0	13.0 $\pm$ 1.2	20.2	13.2 $\pm$ 0.2



SOT-89 Embossed Carrier Tape Outline




Dimensions are in millimeter											
	A0	B0	W	D0	D1	E	F	P0	P1	K0	T
SOT-89 (12mm)	4.8	4.6	12.0	1.55	1.55	1.75	5.5	4.0	8.0	1.65	0.30
	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.2	$\pm$ 0.05	$\pm$ 0.05	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.05	$\pm$ 0.10	$\pm$ 0.05


Notes 10 sprocket hole pitch cumulative tolerance  $\pm$ 0.2.

## TO-252


TO-252 Reel Outline



Dimensions are in millimeter				
Tape Size	A	B	C	W
16mm	330	13.0 $\pm$ 0.5	20.2	16.4 $\pm$ 0.2



TO-252 Embossed Carrier Tape Outline




Dimensions are in millimeter											
	A0	B0	W	D0	D1	E	F	P0	P1	K0	T
TO-252 (16mm)	7.1	10.5	16.0	1.5	1.7	1.75	7.5	4.0	8.0	2.85	0.30
	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.3	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.10	$\pm$ 0.05


Notes 10 sprocket hole pitch cumulative tolerance  $\pm$ 0.2.

## TO-263


TO-263 Reel Outline



Dimensions are in millimeter				
Tape Size	A	B	C	W
16mm	330	13.0 $\pm$ 0.5	20.2	24.4 $\pm$ 0.2



TO-263 Embossed Carrier Tape Outline




Dimensions are in millimeter											
	A0	B0	W	D0	D1	E	F	P0	P1	K0	T
TO-263 (16mm)	10.6	15.8	24.0	1.5	1.6	1.75	11.5	4.0	16.0	4.90	0.30
	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.3	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.1	$\pm$ 0.10	$\pm$ 0.05

Notes

- 10 sprocket hole pitch cumulative tolerance  $\pm$ 0.2.
- A0, B0 and K0 dimensions are determined with respect to EIA RS-481.
- K0 measured from a plane on the inside bottom of the pocket to the top surface of the carrier.

# Tab terminal

## TO-3



- For Outer Carton (L) ; Maximum 5 stacks of partition tray (400pcs) W395×L295×H185mm
- For Outer Carton (S) ; Maximum 2 stacks of partition tray (160pcs) W395×L295×H105mm